



Features

- * $V_{DS} = 30V$, $I_D = 0.85A$
- * $R_{DS(ON)} = \text{Typ } 350m\Omega @ V_{GS} = 4.5V$
- * $R_{DS(ON)} = \text{Typ } 435m\Omega @ V_{GS} = 2.5V$
- * ESD protected
- * DFN1006-3L package

Package and Circuit diagram



DFN1006-3L



Circuit diagram

Marking Diagram



Ordering Information

Part Number	Packaging	Reel Size
PMZ550UNEYL-CN	10000/Tape & Reel	7 inch

Absolute maximum ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 12	V
I_D	Continuous Drain Current ($T_A = 25^\circ\text{C}$)	0.85	A
I_D	Continuous Drain Current ($T_A = 100^\circ\text{C}$)	0.5	A
I_{DM}	Pulsed Drain Current ^{note1}	2.5	A
P_D	Power Dissipation ($T_A = 25^\circ\text{C}$)	0.2	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	625	$^\circ\text{C}/\text{W}$
T_J	Maximum Junction Temperature	$-55 \sim +150$	$^\circ\text{C}$
T_{STG}	Storage Temperature	$-55 \sim +150$	$^\circ\text{C}$

Electrical characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Min	Typ	Max	Unit
Off characteristics						
V _{(BR)DS}	Drain-source breakdown voltage	V _{GS} = 0V, I _D = 250μA	30			V
I _{DS}	Zero gate voltage drain current	V _{DS} = 24V, V _{GS} = 0V			1	μA
I _{GS}	Gate to body leakage current	V _{DS} = 0V, V _{GS} = ±12V			± 10	μA
On characteristics						
V _{GS(th)}	Gate threshold voltage	V _{DS} = V _{GS} , I _D = 250μA	0.6	0.95	1.3	V
R _{DS(on)}	Static drain-source on resistance ^{Note2}	V _{GS} = 4.5V, I _D = 0.5A		350	420	mΩ
		V _{GS} = 2.5V, I _D = 0.3A		435	600	mΩ
Dynamic characteristics						
C _{iss}	Input capacitance	V _{DS} = 15V V _{GS} = 0V f = 1MHz		38.2		pF
C _{oss}	Output capacitance			4.8		pF
C _{rss}	Reverse transfer capacitance			3.3		pF
Q _g	Total gate charge	V _{DS} = 15V I _D = 0.7A V _{GS} = 4.5V		0.9		nC
Q _{gs}	Gate-source charge			0.3		nC
Q _{gd}	Gate-drain charge			0.16		nC
Switching characteristics						
td(on)	Turn-on delay time	V _{DS} = 15V I _D = 0.7A R _{GEN} = 6Ω V _{GS} = 4.5V		5.4		ns
tr	Turn-on rise time			20.2		ns
td(off)	Turn-off delay time			34.4		ns
tf	Turn-off fall time			30.3		ns
Drain-source diode characteristics and maximum ratings						
V _{SD}	Drain to source diode forward voltage	V _{GS} = 0V, I _S = 0.25A		0.9	1.1	V
I _S	Maximum continuous drain to source diode forward current				0.85	A
trr	Body diode reverse recovery time	I _F = 0.25A, di/dt = 100A/μs		24.2		ns
Qrr	Body diode reverse recovery charge			3.2		nC

Notes:1. Repetitive rating: pulse width limited by maximum junction temperature

2. Pulse test: pulse width $\leq 300\mu s$, duty cycle $\leq 0.5\%$

Typical performance characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)




Figure 1. Output Characteristics




Figure 2. On-Resistance vs. I_D




Figure 3. On-Resistance vs. V_{GS}




Figure 4. Gate Threshold Voltage




Figure 5. Drain-Source On Resistance






Figure 6. Source-Drain Diode Forward




V_{DS} - Drain - Source Voltage (V)

Figure 7. Capacitance




Q_g , Total Gate Charge (nC)

Figure 8. Gate Charge Characteristics




T_A - Ambient Temperature (°C)

Figure 9. Power Dissipation




T_A - Ambient Temperature (°C)

Figure 10. Drain Current



V_{DS} - Drain-Source Voltage (V)


Figure 11. Safe Operating Area



t_1 , Square Wave Pulse Duration(s)


Figure 12. $R_{\theta JA}$ Transient Thermal Impedance

Soldering Parameters




Reflow Conditions		Pb-Free Assembly
Pre-heat	-Temperature Min ($T_{S (min)}$)	+150°C
	-Temperature Max ($T_{S (max)}$)	+200°C
	-Time (Min to Max) (t_s)	60-180 secs
Average ramp up rate(Liquid us Temp (T_L) to peak)		3°C/sec. Max
$T_{S (max)}$ to T_L -Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature (T_L) (Liquid us)	+217°C
	-Temperature (t_L)	60-150 secs
Peak Temp (T_P)		+260(+0/-5)°C
Time within 5°C of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6 °C/secs. Max
Time 25°C to Peak Temp (T_P)		8 min. Max
Do not exceed		+260°C

DFN1006-3L Package Outline Drawing




TOP VIEW


SYM	DIMENSIONS					
	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	0.50	0.55	0.60	0.0197	--	0.0236
D	0.55	0.60	0.65	0.0217	0.0236	0.0256
E	0.95	1.00	1.05	0.0374	0.0394	0.0413
D1	0.45	0.50	0.55	0.0177	0.0197	0.0217
E1	0.20	0.25	0.30	0.0079	0.0098	0.0118
e	0.35 BSC					
L	0.20	0.25	0.30	0.0079	0.0098	0.0118
b	0.10	0.15	0.20	0.0039	0.0059	0.0079
G	0.15	0.20	0.25	0.0059	0.0079	0.0098
K	0.35	0.40	0.45	0.0138	0.0157	0.0177



BOTTOM VIEW




SIDE VIEW



SIDE VIEW

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X1	0.70	0.028
X2	0.25	0.010
X3	0.20	0.008
Y1	0.40	0.016
Y2	0.30	0.012
Y3	1.10	0.043

Note:

The land pattern is for reference purposes only.

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。