




SOT-363

特征 Features

- Fast Switching Speed
- Ultra-Small Surface Mount Package
- For General Purpose Switching Applications
- High Conductance

Marking: KJG

机械数据 Mechanical Data

- SOT-363 Small Outline Plastic Package
- Epoxy UL: 94V-0
- Mounting Position: Any

极限值和温度特性(TA = 25°C 除非另有规定)





Maximum Ratings & Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)


Parameters	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	75	V
Working Peak Reverse Voltage	V _{RWM}		
DC Blocking Voltage	V _R		
Average Rectified Output Current	I _O	150	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	I _{FSM}	2	A
Forward Continuous Current	I _{FM}	300	mA
Power Dissipation	P _d	200	mW
Thermal Resistance from Junction to Ambient	R _{θJA}	625	°C/W
Junction Temperature	T _j	125	°C
Storage Temperature	T _{stg}	-55-+150	°C

电特性 (TA = 25°C 除非另有规定)


Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified).

符号 Symbols	参数 Parameter	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
V(BR)R	Reverse Breakdown Voltage	IR=2.5uA	75	---	V
IR	Reverse Leakage Current	VR=75V	---	2.5	uA
		VR=20V		25	nA
VF	Forward Voltage	IF=1mA	---	0.715	V
		IF=10mA		0.855	
		IF=50mA		1	
		IF=150mA	---	1.25	
TRR	Reverse Recovery Time	IF= IR=10mA,	---	4	nS
		Irr=0.1×IR			
		RL=100Ω			
C	Capacitance	VR=0V, f=1MHZ	---	2	pF

Typical characteristics
Forward Characteristics

Reverse Characteristics

Capacitance Characteristics

Power Derating Curve


SOT-363 PACKAGE OUTLINE Plastic surface mounted package

焊盘设计参考Precautions: PCB Design

Recommended land dimensions for SOT-363 diode. Electrode patterns for PCBs



- Note:
1. Controlling dimension: in millimeters.
 2. General tolerance: $\pm 0.05\text{mm}$.
 3. The pad layout is for reference purposes only.

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有限制地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <http://www.chipnobo.com>, or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <http://www.chipnobo.com>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。