


General Purpose Amplifier



Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	BV_{CBO}	60	V
Collector-Emitter Voltage	BV_{CEO}	40	V
Emitter-Base Voltage	BV_{EBO}	5	V
Collector Current	I_C	200	mA
Collector Power Dissipation	P_D	625	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55~+150	°C

Electrical Characteristics (Ta=25°C)

Parameter	Symbol	Conditions	Value			Unit
			Min	Typ	Max	
Collector-base breakdown voltage	BV_{CBO}	$I_C = 10\mu A, I_E = 0$	60			V
Collector-emitter breakdown voltage	BV_{CEO}	$I_C = 1mA, I_B = 0$	40			V
Emitter-base breakdown voltage	BV_{EBO}	$I_E = 10\mu A, I_C = 0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB} = 30V, I_E = 0$			50	nA
Emitter cut-off current	I_{EBO}	$V_{EB} = 5V, I_C = 0$			50	nA
DC current gain	h_{FE}	$V_{CE} = 1V, I_B = 1.0mA$ $V_{CE} = 1V, I_B = 10mA$ $V_{CE} = 1V, I_B = 100mA$	70 100 30		300	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 10mA, I_B = 1.0mA$ $I_C = 50mA, I_B = 5.0mA$			0.2 0.3	V
Base -emitter saturation voltage	$V_{BE(sat)}$	$I_C = 10mA, I_B = 1.0mA$ $I_C = 50mA, I_B = 5.0mA$			0.85 0.95	V
Transition frequency	f_T	$V_{CE} = 20V, I_C = 10mA$	250			MHz

Typical Characteristics




Figure 1. DC current Gain




Figure 2. Saturation Voltage




Figure 3. Base-Emitter Voltage




Figure 4. Current Gain Bandwidth Product




Figure 5. Collector Output Capacitance





Figure 6. Power Derating

Package Dimensions



Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	3.30	3.70	0.130	0.146
A1	2.30	2.70	0.091	0.106
b	0.40	0.50	0.016	0.020
b1	0.50	0.70	0.020	0.028
c	0.35	0.45	0.014	0.018
D	4.45	4.70	0.175	0.185
E	4.40	4.65	0.173	0.183
e	1.17	1.37	0.046	0.054
e1	2.34	2.64	0.092	0.104
L	13.50	14.50	0.531	0.571
L1	1.80	2.20	0.071	0.087

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <https://www.chipnobo.com/en> or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <https://www.chipnobo.com/en>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。