


SOT-23



MARKING: K52

特征 Features

开关速度小于 3uS; Fast Switching Device (TRR <3uS)
最大功率耗散 250mW; Power Dissipation of 250mW
高稳定性和可靠性。High Stability and High Reliability
反向漏电流小。Low reverse leakage

机械数据 Mechanical Data

封装: SOT-23 封装 SOT-23 Small Outline Plastic Package
环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
安装位置: 任意 Mounting Position: Any

极限值和温度特性(TA = 25℃ 除非另有规定)






Maximum Ratings & Thermal Characteristics (Ratings at 25℃ ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
反向电压 Reverse Voltage	VR	85	V
功率消耗 Power Dissipation	Pd	250	mW
工作结温 Operating junction temperature	Tj	150	℃
存储温度 Storage temperature range	Ts	-65-+150	℃
正向电流 Forward continuous Current	IFM	160	mA
Single diode		140	
正向浪涌电流 Repetitive Peak Forward Current	IFRM	500	mA
正向(不重复)浪涌电流 Peak Forward Surge Current; TA=25℃	@tp=1.0us	4.0	A
	@tp=1.0ms	1.0	
	@tp=1.0s	0.5	
典型热阻 Typical thermal resistance	RθJA	500	℃/W

Valid provided that electrodes are kept at ambient temperature.


电特性 Electrical Characteristics (Ratings at 25℃ ambient temperature unless otherwise specified).

符号 Symbols	参数 Parameter	测试条件 Test Condition	界限 Limits			单位 Unit
			Min	Typ	Max	
VRB	反向击穿电压 Reverse Voltage	IB=100uA	85			V
IR	反向漏电流 Reverse Leakage Current	VR=75V			5	nA
VF	正向电压 Forward Voltage	IF=1mA			0.90	V
		IF=10mA			1.00	
		IF=50mA			1.10	
		IF=150mA			1.25	
TRR	反向恢复时间 Reverse Recovery Time	IF= IR=10mA, RL=100Ω IRR=0.1xIR			3	uS
CT	结电容 Capacitance	VR=0V, f=1MHZ		2.0		pF

Typical Characteristics

Fig. 1 Power Derating Curve

Fig. 2 Current Derating Curve

Fig. 3 Typical Forward Characteristics

Fig. 4 Typical Reverse Characteristics
SOT-23 PACKAGE OUTLINE Plastic surface mounted package


SYMBOL	DIMENSIONS	
	MIN	MAX
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

Unit: mm

焊盘设计参考 Precautions: PCB Design(Recommended land dimensions for SOT-23 diode. Electrode patterns for PCBs)


- Note:**
1. Controlling dimension: In millimeters.
 2. General tolerance: $\pm 0.05\text{mm}$.
 3. The pad layout is for reference purposes only.

NOTICE

The information presented in this document is for reference only. Involving product optimization and productivity improvement, ChipNobo reserves the right to adjust product indicators and upgrade some technical parameters. ChipNobo is entitled to be exempted from liability for any delay or non-delivery of the information disclosure process that occurs.

本文件中提供的信息仅供参考。涉及产品优化和生产效率改善，ChipNobo 有权调整产品指标和部分技术参数的升级，所出现信息披露过程存在延后或者不能送达的情形，ChipNobo 有获免责权。

The product listed herein is designed to be used with residential and commercial equipment, and do not support sensitive items and specialized equipment in areas where sanctions do exist. ChipNobo Co., Ltd or anyone on its behalf, assumes no responsibility or liability for any damages resulting from improper use.

此处列出的产品旨在民用和商业设备上使用，不支持确有制裁地区的敏感项目和特殊设备，ChipNobo 有限公司或其代表，对因不当使用而造成的任何损害不承担任何责任。

For additional information, please visit our website <https://www.chipnobo.com/en> or consult your nearest Chipnobo sales office for further assistance.

欲了解更多信息，请访问我们的网站 <https://www.chipnobo.com/en>，或咨询离您最近的 Chipnobo 销售办事处以获得进一步帮助。